



Cable Glands | Measuring devices and controls

- Cable glands and accessories with metric thread
- Cable glands and accessories with Pg-thread
- Cable glands and accessories with NPT- and gas pipe thread
- Explosion-proof cable glands and accessories acc. to ATEX
- HAWKE products
- Technical information

- Brass
- Stainless Steel
- Zinc die-casting
- Plastics
- Accessories from other materials

- Cable gland
- Accessories
- PERFECT
- PERFECT EMV
- WADI
- UNI Dicht
- KOMPAKT
- FAVORIT
- Cable gland with clamping jaw
- Basic
- Flat cable gland

KOMPAKT cable gland
standard /[Characteristics](#) / [Overview](#)

Configuration

Strain relief clamp	Brass, nickel-plated
Bolts	Stainless steel
Washers	Steel, zinc-plated
Sealing ring	SBR/NBR, multiple perforation
Gland body	Brass CuZn39Pb3, nickel-plated
Connecting thread	metric as per EN 60423

Properties

Temperature range	-30°C / +100°C
Protection grade	IP55
Comment	connecting thread long possible on request

Characteristics

Connecting thread standard length

A	C mm	L mm	SW1 mm	SW2 mm	H mm	VPE	Art.-Nr. / Part No.
M12x1,5	4,5 - 8	6	17	17	31,5	100	19.609M12
M16x1,5	6,5 - 12	6	20	20	32	50	19.611M16
M20x1,5	6,5 - 12	6,5	22	22	33	50	19.611M20
M20x1,5	7,5 - 13	6,5	22	22	33,5	50	19.613M20
M25x1,5	8 - 15	7	27	24	35,5	50	19.616M25
M25x1,5	11 - 19	7	30	30	40	50	19.621M25
M32x1,5	17 - 27	8	40	41	39	25	19.629M32
M40x1,5	17 - 28	8	43	41	45,5	25	19.629M40
M50x1,5	27 - 33	9	55	50	52	10	19.636M50
M50x1,5	34 - 39	9	57	57	55,5	5	19.642M50
M63x1,5	38 - 46	10	65	64	57	5	19.648M63


[Metric catalogue download
\(8,5 MB\)](#)
[Pg. NPT catalogue
download \(7,4 MB\)](#)
[General terms and
conditions](#)
[Metal surcharge](#)
[Ex-catalogue \(english\)
download](#)
[Ex catalogue download \(2,1
MB\)](#)

Search

[Imprint](#)[Privacy](#)[Print](#)