



- Company
- Products
- Quality
- Jobs/Career
- News
- Contact

Cable Glands | Measuring devices and controls

- Cable glands and accessories with metric thread
- Cable glands and accessories with Pg-thread
- Cable glands and accessories with NPT- and gas pipe thread
- Explosion-proof cable glands and accessories acc. to ATEX
- HAWKE products
- Technical information

- Brass
- Stainless Steel
- Zinc die-casting
- Plastics
- Accessories from other materials
- Cable gland
- Accessories
- PERFECT
- PERFECT EMV
- WADI
- UNI Dicht
- KOMPAKT
- FAVORIT
- Cable gland with clamping jaw
- Basic
- Flat cable gland

FAVORIT cable gland
standard /[Characteristics](#) / [Overview](#)

Configuration

Bolts	Stainless steel
Washers	Steel, zinc-plated
Sealing ring	SBR/NBR, multiple perforation
Gland body	Brass CuZn39Pb3, nickel-plated
Enlarger	Brass CuZn39Pb3, nickel-plated
Connecting thread	metric as per EN 60423

Properties

Temperature range	-30°C / +100°C
Protection grade	IP55

Comment

connecting thread long possible
on request

Characteristics

Connecting thread standard length

A	C mm	L mm	SW1 mm	SW2 mm	H mm	VPE	Art.-Nr. / Part No.
M12x1,5	5,5 - 8	6	17	20	35,5	100	23.609M12
M16x1,5	6 - 11,5	6	20	24	37	50	23.611M16
M20x1,5	6 - 11,5	6,5	22	24	37,5	50	23.611M20
M20x1,5	8 - 11,5	6,5	22	27	38,5	50	23.613M20
M25x1,5	8,5 - 15	7	27	30	40,5	50	23.616M25
M25x1,5	12 - 19	7	30	34	47,5	25	23.621M25
M32x1,5	17 - 27	8	40	46	51	10	23.629M32
M40x1,5	17 - 27	8	43	46	51	10	23.629M40



[Metric catalogue download
\(8,5 MB\)](#)

[Pg. NPT catalogue
download \(7,4 MB\)](#)

[General terms and
conditions](#)

[Metal surcharge](#)

[Ex-catalogue \(english\)
download](#)

[Ex catalogue download \(2,1
MB\)](#)

[Search](#)

[Imprint](#)

[Privacy](#)

[Print](#)