




Cable Glands | Measuring devices and controls

- Cable glands and accessories with metric thread
- Cable glands and accessories with Pg-thread
- Cable glands and accessories with NPT- and gas pipe thread
- Explosion-proof cable glands and accessories acc. to ATEX
- HAWKE products
- Technical information

- Brass
- Stainless Steel
- Zinc die-casting
- Plastics
- Accessories from other materials
- Cable gland
- Accessories
- PERFECT
- PERFECT EMV
- WADI
- UNI Dicht
- KOMPAKT
- FAVORIT
- Cable gland with clamping jaw
- Basic
- Flat cable gland



Cable glands and accessories with metric thread • Brass • Cable gland • PERFECT

PERFECT cable gland with blanking plug /

[Characteristics](#) / [Overview](#)

Configuration

Blanking plug	Polyamide PA6 GF30
Lamellar insert	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric as per EN 60423

Properties

Temperature range	-20°C / +100°C
Protection grade	IP68
UL / CSA-File	E140310
Comment	details about tests - see annex, blanking plug as single part - see under accessories

Characteristics

Connecting thread standard length

A	L mm	L1 mm	SW1 mm	SW2 mm	H mm	VPE	Art.-Nr. / Part No.
M12x1,5	5	3,5	14	14	28,5	100	50.612 M/V
M16x1,5	5	9	17	17	39	100	50.616 M/V
M20x1,5	6	4,5	22	22	38	100	50.620 M/V
M25x1,5	7	4,5	27	27	41	50	50.625 M/V
M32x1,5	8	4,5	34	34	42,5	25	50.632 M/V
M40x1,5	8	4	43	43	45	10	50.640 M/V
M50x1,5	9	4	55	55	53,5	5	50.650 M/V
M63x1,5	10	4	65	65	56,5	5	50.663 M/V


[Metric catalogue download \(8,5 MB\)](#)
[Pg. NPT catalogue download \(7,4 MB\)](#)
[General terms and conditions](#)
[Metal surcharge](#)
[Ex-catalogue \(english\) download](#)
[Ex catalogue download \(2,1 MB\)](#)
[Search](#)
[Imprint](#)
[Privacy](#)
[Print](#)