



- Company
- Products
- Quality
- Jobs/Career
- News
- Contact

Cable Glands | Measuring devices and controls

- Cable glands and accessories with metric thread
- Cable glands and accessories with Pg-thread
- Cable glands and accessories with NPT- and gas pipe thread
- Explosion-proof cable glands and accessories acc. to ATEX
- HAWKE products
- Technical information

- Brass
- Stainless Steel
- Zinc die-casting
- Plastics
- Accessories from other materials
- Cable gland
- Accessories
- PERFECT
- PERFECT EMV
- WADI
- UNI Dicht
- KOMPAKT
- FAVORIT
- Cable gland with clamping jaw
- Basic
- Flat cable gland

Cable glands and accessories with metric thread • Brass • Cable gland • PERFECT

PERFECT cable gland multiple sealing insert /

[Characteristics / Overview](#)

Configuration	
Lamellar insert	Polyamide PA6 V-2
Sealing insert	Evoprene TPE
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric as per EN 60423
Properties	
Temperature range	-20°C / +100°C
Protection grade	IP65 when diameters of the holes in the sealing insert and the cable diameters are almost identical
Comment	please indicate required sealing insert, e.g. 50.612 M/4x2 sealing inserts - see under accessories - series WJ-DM xx/zXz



Characteristics

Connecting thread standard length

A	L mm	SW1 mm	SW2 mm	H mm	VPE	Art.-Nr. / Part No.
M12x1,5	5	14	14	25	100	50.612 M/zXz
M16x1,5	5	17	17	30	100	50.616 M/zXz
M20x1,5	6	22	22	33,5	100	50.620 M/zXz
M25x1,5	7	27	27	36,5	50	50.625 M/zXz
M32x1,5	8	34	34	38	25	50.632 M/zXz
M40x1,5	8	43	43	41	10	50.640 M/zXz

[Metric catalogue download \(8,5 MB\)](#)

[Pg. NPT catalogue download \(7,4 MB\)](#)

[General terms and conditions](#)

[Metal surcharge](#)

[Ex-catalogue \(english\) download](#)

[Ex catalogue download \(2,1 MB\)](#)

Search

[Imprint](#)

[Privacy](#)

[Print](#)