



- Cable glands and accessories with metric thread
- Cable glands and accessories with Pg-thread
- Cable glands and accessories with NPT- and gas pipe thread
- Explosion-proof cable glands and accessories acc. to ATEX
- HAWKE products
- Technical information

Cable Glands | Measuring devices and controls

- Brass
- Stainless Steel
- Zinc die-casting
- Plastics
- Accessories from other materials
- Cable gland
- Accessories
- PERFECT
- PERFECT EMV
- WADI
- UNI Dicht
- KOMPAKT
- FAVORIT
- Cable gland with clamping jaw
- Basic
- Flat cable gland

Cable glands and accessories with metric thread • Brass • Cable gland • PERFECT

[PERFECT cable gland enlarged sealing and clamping range /](#)

[Characteristics / Overview](#)

Configuration

Lamellar insert	Polyamide PA6 V-2
Sealing ring	Polychloroprene-Nitrile rubber CR/NBR
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric as per EN 60423

Properties

Temperature range	-20°C / +100°C
Protection grade	IP68 - 5 bar / IP69K*
Test standard	UL 514B
UL / CSA-File	E140310
Comment	details about tests - see annex

Characteristics

Connecting thread standard length

A	C mm	L mm	SW1 mm	SW2 mm	H mm	VPE	Art.-Nr. / Part No.
M12x1,5	5 - 8	6,5	17	19	31,5	100	50.612/16 M
M16x1,5	9 - 12	5	22	22	32,5	100	50.616/20 M
M20x1,5	11 - 16	6	27	27	35,5	50	50.620/25 M
M25x1,5	14 - 21	7	34	34	37	25	50.625/32 M
M32x1,5	19 - 27	8	43	43	41	10	50.632/40 M



[Metric catalogue download \(8,5 MB\)](#)

[Pg. NPT catalogue download \(7,4 MB\)](#)

[General terms and conditions](#)

[Metal surcharge](#)

[Ex-catalogue \(english\) download](#)

[Ex catalogue download \(2,1 MB\)](#)

Search

[Imprint](#)

[Privacy](#)

[Print](#)