


Nickel Plated Brass PG Cable Glands

Range: Cable Glands/Grommets

Order Code: GCG-BMS-PG16-NP (50.016)





DESCRIPTION

Perfect cable gland PG16 thread length 6.5, min/max cable dia 10-14

CABLE GLANDS/GROMMETS FEATURES

- PG Nickel Plated Brass
- Easy to install
- 50.0xx range offers protection against twisting and also offers integrated anchorage
- · EMC Versions available

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

MAKING THE RIGHT CONNECTIONS

hylec

SPECIFICATION

Product Type	Standard
Sealing Ring Material	Polychloroprene-Nitrile rubber CR/NBR
Body Material	Nickel Plated Brass
Min Temperature Rating °C	-20
Max Temperature Rating °C	100
IP Rating	68
Thread Size	PG16
Clamping Range Min (mm)	10
Clamping Range Max (mm)	14
Lamellar Insert Material	Polyamide PA6 V-2
External Connecting Thread Type	PG
Thread Length (mm)	6.5
Width Across Flat 1 (mm)	24
Width Across Flat 2 (mm)	24
Height (mm)	31.5
Connecting Thread Size	Pg 16
Additional Material Detail	Body - Brass CuZn39Pb3 nickel plated, O-Ring - Nitrile rubber

