


# Range: Cable Glands/Grommets

Order Code: GCG-NPS-PG48-GD (50.048 PA)





#### **DESCRIPTION**

Perfect cable gland PA7001 PG48 thread length 14, min/max cable dia 34-44

#### **CABLE GLANDS/GROMMETS FEATURES**

- PG Nylon
- · Easy to install
- 50.0xx range offers protection against twisting and also offers integrated anchorage
- Temperature rating -20°C to +100°C

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



### **SPECIFICATION**

| Product Type                    | Standard                               |
|---------------------------------|--|
| Sealing Ring Material           | Polychloroprene-Nitrile rubber CR/NBR  |
| Body Material                   | Polyamide                              |
| Min Temperature Rating °C       | -20                                    |
| Max Temperature Rating °C       | 100                                    |
| IP Rating                       | 68                                     |
| Colour                          | Dark Grey - RAL 7001                   |
| Thread Size                     | PG48                                   |
| Clamping Range Min (mm)         | 34                                     |
| Clamping Range Max (mm)         | 44                                     |
| External Connecting Thread Type | PG                                     |
| Thread Length (mm)              | 14                                     |
| Comments                        | details about test standards see annex |
| Width Across Flat 1 (mm)        | 65                                     |
| Width Across Flat 2 (mm)        | 65                                     |
| Height (mm)                     | 67                                     |
| Connecting Thread Size          | Pg 48                                  |
| Additional Material Detail      | Body - Polyamide PA6 V-2               |
| Standards                       | UL514B                                 |
| Test Standard                   | UL 514B                                |

## **INDUSTRY ACCREDITATIONS**



