

# Contactors

## Range: Motor Control Gear

Order Code: DEC-80D11/415VAC



### DESCRIPTION

3 pole contactor, AC1 125A,415V AC coil

### MOTOR CONTROL GEAR FEATURES

- CSA, CE, UL(listed)
- C/W instantaneous auxiliary contact
- Temperature range of -20°C to +85°C
- Combi Head Ready to Tighten Screws
- Compact design
- Heavy duty pure silver point contact
- IP20 finger protected screws

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

|                                      |           |
|--------------------------------------|-----------|
| <b>Weight</b>                        | 1.43      |
| <b>Length (mm)</b>                   | 129       |
| <b>Width (mm)</b>                    | 81.7      |
| <b>Height (mm)</b>                   | 123       |
| <b>Three Phase Load at 240V (kW)</b> | 25        |
| <b>Three Phase Load at 380V (kW)</b> | 45        |
| <b>Three Phase Load at 400V (kW)</b> | 45        |
| <b>Three Phase Load at 440V (kW)</b> | 45        |
| <b>Three Phase Load at 575V (kW)</b> | 45        |
| <b>Aux Contact Number</b>            | 2         |
| <b>Aux Contact Type</b>              | N/O + N/C |
| <b>Series</b>                        | DEC       |
| <b>Voltage (VAC)</b>                 | 415       |