



# Pillar Terminal Blocks

## Range: Emech Terminals/Accessories

Order Code: CTS-INA-F08-W10 (HY431/1 NYFLP)



### DESCRIPTION

1 pole natural polyamide PA6.6 wire protected pillar terminal block 8mm pitch 17.5a 450v

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

|                                       |                          |
|---------------------------------------|--------------------------|
| <b>Number of Poles</b>                | 1                        |
| <b>Terminal Material</b>              | OT58 nickel plated       |
| <b>Terminal Type</b>                  | Wire Protected           |
| <b>Body Material</b>                  | Polyamide PA6.6          |
| <b>Colour</b>                         | Natural                  |
| <b>Glow Wire Resistance Test Temp</b> | GWIT775°C (EN60695-2-13) |
| <b>Max Conductor Size (Sq mm)</b>     | 1.5                      |
| <b>Max Current (A)</b>                | 17.5                     |
| <b>Max Voltage (V)</b>                | 450                      |
| <b>Working Temperature</b>            | 110                      |
| <b>Pitch (mm)</b>                     | 8                        |
| <b>Height (mm)</b>                    | 12.3                     |
| <b>Width (mm)</b>                     | 16.4                     |
| <b>Length (mm)</b>                    | 6                        |
| <b>Diameter (mm)</b>                  | 2.6                      |
| <b>Flammability Rating</b>            | UL94V2 and GWIT775°C     |
| <b>Terminal Screw Material</b>        | White zinc plated steel  |
| <b>Wire Protection Material</b>       | Stainless steel          |

## INDUSTRY ACCREDITATIONS

