Micro TeePlug & Sockets

Range: Weatherproof/Waterproof Connectors

Order Code: CWP-PMM-LA-02A (THB.381.N2B)



DESCRIPTION

Micro Plug M16 2 pole Screw terminal IP68/69K 10A 500V 1 cable entry

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization Â- a diameter of only 14mm (2 poles)
- Screw connection for field wiring (M2 screws max 0.2 Nm) and versatility guaranteed during installation
- Available with overmolded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



SPECIFICATION

Туре	Plug
Cable Entries	1
Max Current (A)	10
Max Voltage (V)	500
Number of Poles	2
IP Rating	68/68K
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

INDUSTRY ACCREDITATIONS



