



Micro TeePlug & Sockets

Range: Weatherproof/Waterproof Connectors

Part Number: THB.381.A3E



DESCRIPTION

Micro Plug 3 pole Screw terminal 7mm to 8.0mm cable diameter, IP68, 10A, 500V, 1 cable entry. Cable markings: L-N-E

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization □ a diameter of only 14mm (3 poles)
- Screw connection for field wiring (M2 screws - max 0.2 Nm) and versatility guaranteed during installation
- Available with over-molded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high-pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Type	Plug
Cable Entries	1
Max Current (A)	10
Max Voltage (V)	500
Number of Poles	3
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	8
IP Rating	IP66/IP68 (5m/1h)/IP69
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

INDUSTRY ACCREDITATIONS

