

Micro TeePlug & Sockets

Range: Weatherproof/Waterproof Connectors

Order Code: CWP-PMS-DB-P03O (THB.381.B3E)



DESCRIPTION

Micro Socket 3 pole Screw terminal 7mm to 8.0mm cable diameter, IP68/IP69K, 10A, 500V, 1 cable entry. Contact marking: L-N-E

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Miniaturization Â- a diameter of only 14mm (3poles)
- Screw connection for field wiring (M2 screws max 0.2 Nm) and versatility guaranteed during installation
- · Available with over-molded cable
- Tested and approved to resist dust and water (IP68 30m/1h) and high-pressure water (IP69K)
- Suitable For Class 2 Applications (Double Insulated) Max. 250V AC.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

hylec

MAKING THE RIGHT CONNECTIONS

SPECIFICATION

Туре	Socket
Cable Entries	1
Max Current (A)	10
Max Voltage (V)	500
Number of Poles	3
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	8
IP Rating	IP66/IP68 (5m/1h)/IP69
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 GF UL94 V0
Fixing System	Cable
Terminal Type	Silver-plated brass (zinc-plated screws)

INDUSTRY ACCREDITATIONS



