


## 1010M80

Wadi cable gland M80 thread length 18, min/max cable dia 53-60 Body - Brass CuZn39Pb3 nickel plated, O-Ring - Nitrile rubber



### SPECIFICATION

|  |   |
|--|---|
| <b>Product Type</b>                    | Standard  |
| <b>Body Material</b>                   | Nickel Plated Brass   |
| <b>Min Temperature °C</b>              | -30   |
| <b>Max Temperature °C</b>              | 100   |
| <b>IP Rating</b>                       | 65  |
| <b>Thread Size</b>                     | M80   |
| <b>Clamping Range Min (mm)</b>         | 53  |
| <b>Clamping Range Max (mm)</b>         | 60  |
| <b>External Connecting Thread Type</b> | Metric  |
| <b>Thread Length (mm)</b>              | 18  |
| <b>Sealing Insert</b>                  | Polychloroprene-Nitrile rubber CR/NBR                         |
| <b>Washer Material</b>                 | Brass, nickel-plated  |
| <b>Width Across Flat 1 (mm)</b>        | 90  |
| <b>Width Across Flat 2 (mm)</b>        | 90  |
| <b>Height (mm)</b>                     | 60  |
| <b>Connecting Thread Size</b>          | M80x2.0   |
| <b>Additional Material Detail</b>      | Body - Brass CuZn39Pb3 nickel plated, O-Ring - Nitrile rubber |