


# **Emergency Stop Stations**

### **Range: Control Stations**

Order Code: SCS-PSK-GY-RXX (1DE.01.03AG)





\*Enclosure only except 1DE .SP series where D includes actuator height

#### DESCRIPTION

E-stop c/w key reset, yellow cover, grey base, red mushroom head EN418

### **CONTROL STATIONS FEATURES**

- Customised control station service available please ask for details.
- Insulation resistance >100MOhm @ 500VDC
- · Enclosures sealed up to IP56
- Unique snap on Din Rail and Flange brackets
- · Dust & waterproof for short-term submersion
- 4 sizes available! Accepting 1-4 push button switches
- 2 contact blocks fitted as standard
- · Different voltage ratings are available
- · Contact material Silver Bifurcated and serrated
- Operating Temperature -10 to +65°C
- Contact rating AC12 Resistive / AC15 Electromagnetic 240V (3A) / 415V (1.5A)
- Mechanical life 1 million operations

Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

## hylec

### MAKING THE RIGHT CONNECTIONS

#### **SPECIFICATION**

Accessories Available	DIN rail and flange snap-on brackets
Base Colour	Grey
Base Style	Standard base
Depth (mm)	53
Enclosure Material	ABS-UL94-HB
Height (mm)	80
IP Rating	IP56
Lid Colour	Yellow
Min Temperature Rating °C	-10
Max Temperature Rating °C	65
Number of Switches	1
Size (mm)	80x73x53
Switch 1 Style	Pushbutton non-illuminated, key reset
Switch 1 Substyle	Mushroom head key reset
Width (mm)	73

### **INDUSTRY ACCREDITATIONS**



MAKING THE RIGHT CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

