



Switches

Range: Switches and Lamps

Order Code: DSS22-K322



Product Image
Not Available

DESCRIPTION

Key 3 position selector 2a 2b

SWITCHES AND LAMPS FEATURES

- Non Illuminated push button switches available with 12 different heads
- All switches complete with 1 NO and 1 NC contact blocks
- Mechanical life - 1 million operations
- Contact material - Silver Bifurcated and serrated
- Contact rating - AC12 Resistive / AC15 Electromagnetic - 240V (3A) / 415V (1.5A)
- Choice Of Cap colours
- Insulation resistance - >100MOhm @ 500VDC
- Different voltage ratings are available
- Operating Temperature -10 to +65°C

Features may vary by product throughout the range.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Button Head Material	Polycarb VO
Body Material	PA66 + 15% GF-VO
Locknut Material	PA66 V2 +15%GF
Number of Contact Blocks	2
Selector Switch Positions	3 Position 45 Degree
Shaft Style	Standard
Max Wire Size Single Strand (Sq mm)	2.5
Max Wire Size Multi Strand (Sq mm)	1.5
Min Temperature Rating °C	-10
Max Temperature Rating °C	65
Panel Hole Size	22.5mm
IP Rating	56
Key Material	Brass, Nickel Plated
Product Sub Type	Key 2 and 3 positions
Product Type	Selector and non-illuminated switches
Terminal Type	Screw clamp