
# TeeTube

# Range: Weatherproof/Waterproof Connectors

Part Number: THB.390.A3B





### **DESCRIPTION**

TeeTube Mini 2 Pole Screw - wp 7mm to 13.5mm, 2.5 mm max conducter size IP68 24A 450V 2 cable entries

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



### **SPECIFICATION**

Туре	Joint connector (re-usable/re-accessible)
Colour	Black
Length (mm)	82
Width (mm)	32
Cable Entries	2
Max Current (A)	24
Max Voltage (V)	450
Number of Poles	2
Min Conductor Size (Sq mm)	0.25
Max Conductor Size (Sq mm)	2.5
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	13.5
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T85
Body Material	PA66 / TPE
Corrosion Resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test
	Ka (168h)
Fixing System	Cable
Terminal Type	Screw with push-wire clamp (M3 - max. 0.5 Nm)

## **INDUSTRY ACCREDITATIONS**



