# TeeTube


# reerube

Range: Weatherproof/Waterproof Connectors

Order Code: THB.390.B1A



Product Image Not Available



### **DESCRIPTION**

TeeTube Mini "Elbow shape" 3 Pole Screw - end barrier contact 7mm to 13.5mm, 4 mm max conducter size IP68 32A 450V 2 cable entries

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



# **SPECIFICATION**

| Туре                        | Joint connector (re-usable/re-accessible)                             |
|-----------------------------|---|
| Colour                      | Black   |
| Length (mm)                 | 73  |
| Width (mm)                  | 32  |
| Depth (mm)                  | 61  |
| Cable Entries               | 2   |
| Max Current (A)             | 32  |
| Max Voltage (V)             | 450   |
| Number of Poles             | 3   |
| Min Conductor Size (Sq mm)  | 0.5   |
| Max Conductor Size (Sq mm)  | 4   |
| Minimum Cable Diameter (mm) | 7   |
| Maximum Cable Diameter (mm) | 13.5  |
| IP Rating                   | 68  |
| Min Temperature Rating °C   | -40   |
| Max Temperature Rating °C   | 125   |
| Temperature "T" Rating      | T85   |
| Body Material               | PA66 GF UL94 V0 GWT 960°C   |
| Corrosion Resistance        | Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test |
|                             | Ka (168h)   |
| Fixing System               | Cable   |
| Terminal Type               | Screw (M3 - max. 0.5 Nm)  |

# **INDUSTRY ACCREDITATIONS**



