
TeeTube

Range: Weatherproof/Waterproof Connectors

Part Number: THB.390.D3C.5





DESCRIPTION

TeeTube with innovative cable glands, 3 Pole Screw - wp 10.5mm to14mm on one gland 14mm to 17mm on the other gland, 2.5 mm max conducter size IP68 24A 450V 2 cable entries

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C
 Features may vary by product throughout the range.

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.



SPECIFICATION

| Cable Entries | 2 |
|-----------------------------|------------|
| Max Current (A) | 24 |
| Max Voltage (V) | 450 |
| Number of Poles | 3 |
| Max Conductor Size (Sq mm) | 2.5 |
| Minimum Cable Diameter (mm) | 10.5 |
| Maximum Cable Diameter (mm) | 17 |
| IP Rating | 68 |
| Min Temperature Rating °C | -40 |
| Max Temperature Rating °C | 125 |
| Temperature "T" Rating | T125 |
| Body Material | PA66 / TPE |
| Fixing System | Cable |
| Terminal Type | Screw - wp |

INDUSTRY ACCREDITATIONS



