




# TeeTube

## Range: Weatherproof/Waterproof Connectors

Order Code: CWP-TIS-ADS-A02 (THB.391.A2A)



### DESCRIPTION

TeeTube Mini 2 Pole Screw - end barrier contact 7mm to 12mm, 4 mm max conductor size IP68 32A 450V 2 cable entries

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

*Features may vary by product throughout the range.*

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

Cable Entries	2
Max Current (A)	32
Max Voltage (V)	450
Number of Poles	2
Max Conductor Size (Sq mm)	4
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	12
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 / PBT / TPE
Fixing System	Cable
Series	TH391
Terminal Type	Screw - end barrier contact

## INDUSTRY ACCREDITATIONS

