


## Range: Weatherproof/Waterproof Connectors

Order Code: CWP-TYG-CCS-C04 (THB.399.D4A)





### DESCRIPTION

TeeTube 4 Pole Screw - end barrier contact 8mm to 17mm , 4 mm max conducter size IP68 32A 250V 3 cable entries

### WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

# hylec 🖌

### MAKING THE RIGHT CONNECTIONS

#### **SPECIFICATION**

Cable Entries	3
Max Current (A)	32
Max Voltage (V)	250
Number of Poles	4
Max Conductor Size (Sq mm)	4
Minimum Cable Diameter (mm)	7
Maximum Cable Diameter (mm)	17
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T85
Body Material	PA66 / TPE
Fixing System	Cable
Terminal Type	Screw - end barrier contact

### **INDUSTRY ACCREDITATIONS**



MAKING THE RIGHT CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

