


TeeTube

Range: Weatherproof/Waterproof Connectors

Order Code: THB.399.G3C.5





DESCRIPTION

TeeTube with innovative cable gland 3 Pole Screw - wp contact 10.5mm to 14mm on one gland 14mm to 17mm on the other 2 glands, 4 mm max conducter size IP68 32A 250V 3 cable entries

WEATHERPROOF/WATERPROOF CONNECTORS FEATURES

- Tough, robust construction with large cable range acceptance
- Straight through, T splitter and Y splitter versions available
- Dual terminal versions available for easy fitting and looping of conductors (2+2 and 3+3 poles)
- Temperature rating of -40°C to +125°C

Features may vary by product throughout the range.

Subject to technical modification without notice. Typographical and other errors do not justify claim for damages.

hylec

MAKING THE RIGHT CONNECTIONS

SPECIFICATION

Cable Entries	3
Max Current (A)	24
Max Voltage (V)	250
Number of Poles	3
Max Conductor Size (Sq mm)	2.5
Minimum Cable Diameter (mm)	10.5
Maximum Cable Diameter (mm)	17
IP Rating	68
Min Temperature Rating °C	-40
Max Temperature Rating °C	125
Temperature "T" Rating	T125
Body Material	PA66 / TPE
Fixing System	Cable
Terminal Type	Screw - wp

INDUSTRY ACCREDITATIONS



MAKING THE RIGHT CONNECTIONS WWW.HYLEC-APL.COM | SALES@HYLEC-APL.COM | 01933 234400

