

Door Enclosures

Range: Enclosures

Order Code: EDE-PLA-030-040-017-GL (DED004)



DESCRIPTION

IP65, IK08 Lockable solid door plastic enclosure 400x300x170

ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustibility standards IP65 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

Subject to technical modification without notice.

Typographical and other errors do not justify claim for damages.

SPECIFICATION

Product Type	Solid door enclosures
Door Style	Solid
Enclosure Material	ABS-HB
Door Material	ABS-HB
IP Rating	65
Colour	Grey (RAL 7035)
Min Temperature Rating °C	-20
Max Temperature Rating °C	85
Height (mm)	400
Width (mm)	300
Depth (mm)	170
Mounting Plate (mm)	245x350x1
Number of Locks	2
Comments	Lockable, with galvanized steel back plate and wall mounting brackets supplied
Accessories Available	Kwik fix cable gland

INDUSTRY ACCREDITATIONS

