

# Door Enclosures

## Range: Enclosures

Order Code: EDE-PLA-050-070-025-GT (DED020)



### DESCRIPTION

IP65, IK08 Lockable transparent door plastic enclosure 700x500x250

### ENCLOSURES FEATURES

- Available in 10 sizes
- Made from UL approved ABS-HB Flame Retardant plastic
- Designed to meet protection and combustible standards IP65 and IK08
- Comes complete with steel back plate and mounting brackets
- Supplied in grey (RAL 7035) body with solid or transparent door
- Suitable for use in sea salt air conditions and dry dust environments
- Temperature range of -20° to +85°

*Subject to technical modification without notice.*

*Typographical and other errors do not justify claim for damages.*

## SPECIFICATION

Product Type	Transparent door enclosures
Door Style	Transparent
Enclosure Material	ABS-HB
Door Material	Polycarbonate
IP Rating	65
Colour	Grey (RAL 7035)
Min Temperature Rating °C	-20
Max Temperature Rating °C	85
Height (mm)	700
Width (mm)	500
Depth (mm)	250
Mounting Plate (mm)	442x645x1
Number of Locks	2
Comments	Lockable, with galvanized steel back plate and wall mounting brackets supplied
Accessories Available	Kwik fix cable gland

## INDUSTRY ACCREDITATIONS

